

PRODUCT DATASHEET

TRIPROOF 48 W - 4000 K – IP65 – 150CM

Item Nr 180924056-1

Tri Proof Professional – Polycarbonate material



APPLICATION

- Replacement of old technology TriProofs
- Parkings
- Building facades
- Garage, Car port
- The design is made according the EN for fire-risk – for example accumulation of dust.

PRODUCT BENEFITS

- A high quality Polycarbonate Cover and Acrylonitrile Butadiene Styrene housing
- 50% Energy saving compare to traditional T8 tubes
- 5 years warranty

PRODUCT FEATURES

- Lumen efficiency up to 95 Lumen / Watt
 - Symmetrical beam angle 120°
 - Mounting by stainless steel clips
 - Type of protection : IP65
 - Impact resistance : IK08 for cover, IK06 for body
 - Working temperature : -20° up to +40°
 - Connection via IP65 cable glands on 1 sides
-

TECHNICAL DATA

Electrical data

Nominal wattage	48 Watt
Operating mode	Non-Isolated Driver
Nominal Voltage	175 – 250 Volt
Power Factor	>0,5
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 Kelvin
Luminous flux	4560 lm
Luminous efficiency	95 lm/watt
Color matching / deviation	<7
Denomination of the color	Day light
CRI (Color rendering Index Ra)	>80

Dimension & weight



Lenght	1560 mm
Thikness	96 mm
Height	80 mm
Weight	2.3kg
Cable Type and lenght	

Color & material

Body material	Acrylonitrile Butadiene Styrene
Product Color	Transparent / Grey
Housing	Grey
Front Glass	Transparent

Temperature & operation

Working temperatures	Minus 20° up to 40° Celcius
----------------------	-----------------------------


Different product data

Mounting location	Wall / Floor
Dimmable	No
Connection	By Cable H05 – 3G1,5 – L N Earth
LED module	SMD Not replacable
LED Brand	
Driver	Non-Isolated
Lifetime	25000 at 25° Celcius
ON/OFF tests	100000

Certifications

Impact protection class	IK08 for cover, IK06 for body
Glow wire according IEC 695-2-1	
Photobiological safety group EN62778	
Photobiological safety group accessories EN62471	
Protection class	
Insulation protection	IP65
Limited temperature class	
CE Certifications	CE/EMC/LVD/RoHS

Light distribution curve



Item	Ean Code	Packaging	Dimensions	Gross weight
180924056-1	5420080906002	Carton / Shrink	160x32.5x21.5cm	19.4kgs

For all other questions, please contact our commercial division : info@ethos-europe.com