

## VERIFICATION OF COMPLIANCE

No.: LVD GZES1912029768LM

Applicant: Glamor Optoelectronics Technology Co., Ltd

3, Guangfeng Industrial Park, West District, Zhongshan,

Guangdong, China

Manufacturer: Glamor Optoelectronics Technology Co., Ltd

3, Guangfeng Industrial Park, West District, Zhongshan,

Guangdong, China

Product Name: LED Strip Light

Product Description: LED lighting chain

Model No.: See page 2
Trade Mark: GLAMOR

Rating: 220 V - 240 V; 50 Hz / 60 Hz; other information see page 2

Protection against Electric Shock: Class II

Degree of Protection: IP65

Additional Information: Suitable for direct mounting on normally flammable surfaces.

RG1 Non replaceable LEDs

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: EN 60598-2-21: 2015

EN 60598-1: 2015 + A1: 2018

EN 62493: 2015

as shown in the

Test Report Number(s): GZES191202976801

This Verification of Compliance has been granted to the applicant based on the results of tests, performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant harmonized standards under the Low Voltage Directive 2014/35/EU. The CE marking as shown below can be affixed, under the responsibility of the manufacturer, after completion of an EC Declaration of Conformity and compliance with all relevant EC Directives. The affixing of the CE marking presumes in addition that the conditions in annexes III and IV of the Directive are fulfilled.



2020-03-10

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)



No.:

Rating:

## LVD GZES1912029768LM

## Other information added:

| rmation added: |                |                         |                               |                     |
|----------------|----------------|-------------------------|-------------------------------|---------------------|
|                | models         | wattage per meter (W/m) | "X" represents the length of  | Max. wattage<br>(W) |
|                |                |                         | product (increase 1 per step) |                     |
|                | ST2835-60S-X,  | 5 W/m                   | Max. 96 m                     | 480 W               |
|                | BW2835-60S-X   |                         |                               |                     |
|                | ST2835-120S-X, | 9 W/m                   | Max. 53 m                     | 477 W               |
|                | ST5050-60S-X,  |                         |                               |                     |
|                | ST5730-60S-X,  |                         |                               |                     |
|                | ST5730-120S-X, |                         |                               |                     |
|                | ST2835-120D-X, |                         |                               |                     |
|                | BW2835-120S-X, |                         |                               |                     |
|                | BW5050-60S-X,  |                         |                               |                     |
|                | BW5730-60S-X,  |                         |                               |                     |
|                | BW5730-120S-X, |                         |                               |                     |
|                | BW2835-120D-X  |                         |                               |                     |
|                | ST5730-120D-X, | 13 W/m                  | Max. 36 m                     | 468 W               |
|                | BW5730-120D-X  |                         |                               |                     |
|                | ST2835-180T-X, | 15 W/m                  | Max. 32 m                     | 480 W               |
|                | ST5730-180T-X, |                         |                               |                     |
|                | BW2835-180T-X, |                         |                               |                     |
|                | BW5730-180T-X  |                         |                               |                     |



2020-03-10

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services, printed overleaf.

Member of SGS Group (Société Générale de Surveillance)