

PRODUCT DATASHEET

LIGHT @ Rechargeable Work Light 3W - 6500 K – IP20

Item Nr 622510123

Worklight



APPLICATION

Where you need good local light

PRODUCT BENEFITS

- aluminium housing, to be safety working at construction site
- 80% Energy saving compare to halogen
- IP20
- 1 years warranty

PRODUCT FEATURES

- Lumen efficiency up to 70 Lumen / Watt
- Type of protection : IP20
- Impact resistance: N/A
- Working temperature: -20° up to +45°
- 1pc 450mAh battery included
- With magnet and clip

TECHNICAL DATA


Electrical data

Nominal wattage	3 Watt
Operating mode	White led on-red led on-red led flash-off
Nominal Voltage	Input 5V
Power Factor	N/A
Mains frequency	N/A

Photometrical data

Color temperature	6500K
Luminous flux	200 lm
Luminous efficiency	70 lm/watt
Color matching / deviation	Blue
Denomination of the color	Cool White
CRI (Color rendering Index Ra)	>65-70

Dimension & weight



Length	24 mm
Thickness	10 mm
Height	122 mm
Weight	37g
Cable Type and length	1pc 5V 1A USB cable included, no charger

Color & material

Body material	Aluminium
Product Color	Blue
Housing	Blue
Front Glass	The lens is PC

Temperature & operation

Working temperatures	Minus 20° up to 45° Celcius
----------------------	-----------------------------


Different product data

Mounting location	Every where. It is portable lamp
Dimmable	yes
Connection	
LED module	COB Not replacable
LED Brand	No brand.
Driver	N/A
Lifetime	50000 at 25° Celcius
ON/OFF tests	10000

Certifications

Impact protection class	N/A
Glow wire according IEC 695-2-1	
Photobiological safety group EN62778	
Photobiological safety group accessories EN62471	led has EN62471 certificate
Protection class	
Insulation protection	IP20
Limited temperature class	
CE Certifications	CE(EMC)/RoHS

Light distribution curve



Item	Ean Code	Packaging	Dimensions	Gross Weight
622510123		Carton	33 x 30 x 19cm	6.3kg

For all other questions, please contact our commercial division : info@ethos-europe.com