

REPORT No.: R2DG2001132326E Date: January 16, 2020 Page 1 of 5

BAREBONES SYSTEMS,LLC.

1215 East Wilmington Avenue-Ste.140 Salt Lake City, UT 84106

Report on the submitted samples said to be:

Sample Name : Felt Lantern Bag

Style/Item No : LIV-279
Country of Origin : China

Sample Receiving Date : January 13, 2020

Testing Period : From January 13, 2020 to January 16, 2020

Results : Please refer to next page(s).

Signed for and on behalf of BACL

Checked by:

Jane Xu

Technical Supervisor

me

Approved by:

Bensen Huang Laboratory Manager



RE	PORT No.: R2DG2001132326E	Date: January 16, 2020	Page 2 of 5				
**** Sur	**************************************						
<u>TE</u>	ST REQUEST		CONCLUSION				
Α	US California Proposition 65. on Lead content		Pass				
В	US California Proposition 65. on Phthalates (DBP、BBP content	DEHP、DnHP、DINP and DIDP)	Pass				
Pas	Pass= Meet the Requirement of Client						



REPORT No.: R2DG2001132326E Date: January 16, 2020 Page 3 of 5

Results:

Tested part(s):

- (1) Tan coated leather(body patch)
- (2) Rust metal(stopper body)
- (3) Rust metal(stopper press-button)
- (4) Rust metal(spring)
- (5) Tan coating (edge of body patch)

A. US California Proposition 65. on Lead content

Total Lead Content (In surface-coating)

<u>Test method:</u> With reference to CPSC-CH-E1003-09.1, by acid digestion and analysis was performed by Inductively Coupled Plasma-Optical Emission Spectrometer (ICP-OES) or Atomic Absorption Spectrometry (AAS).

Itom	Unit	MDL	Results	Client's Limit
Item			(5)	Client's Limit
Lead (Pb)	mg/kg	10	N.D.	90
Conclusion	1	1	Pass	1

Total Lead Content (In substrate)

<u>Test method:</u> With reference to CPSC-CH-E1001-08.3/ CPSC-CH-E1002-08.3, by acid digestion and analysis was performed by Inductively Coupled Plasma-Optical Emission Spectrometer (ICP-OES) or Atomic Absorption Spectrometry (AAS).

liam.	Unit	MDL	Results				Client's Limit
Item			(1)	(2)	(3)	(4)	Client's Limit
Lead (Pb)	mg/kg	10	N.D.	67	33	28	300
Conclusion	1	1	Pass	Pass	Pass	Pass	1

Note:

- N.D. = Not Detected or less than MDL
- MDL = Method Detection Limit
- mg/kg=ppm
- Photo is included.



REPORT No.: R2DG2001132326E Date: January 16, 2020 Page 4 of 5

B. US California Proposition 65. on Phthalates (DBP, BBP, DEHP, DnHP, DINP and DIDP) content

<u>Test method:</u> With reference to CPSC-CH-C1001-09.4, by solvent extraction and Analysis was performed by gas chromatographic-mass spectrometer (GC-MS)

ltom	Unit	MDL	Res	Client's	
Item	Unit		(1)	(5)	Limit
Dibutyl Phthalate (DBP)	mg/kg	30	N.D.	N.D.	1000
Benzylbutyl Phthalate (BBP)	mg/kg	30	N.D.	N.D.	1000
Bis-(2-ethylhexyl) Phthalate (DEHP)	mg/kg	30	N.D.	N.D.	1000
Di-n-hexyl Phthalate (DnHP)	mg/kg	30	N.D.	N.D.	1000
Diisononyl Phthalate (DINP)	mg/kg	100	N.D.	N.D.	1000
Diisodecyl Phthalate (DIDP)	mg/kg	100	N.D.	N.D.	1000
Conclusion	1	1	Pass	Pass	/


Note:

- N.D. = Not Detected or less than MDL
- MDL = Method Detection Limit
- % = Percentage by weight
- -0.1% = 1000 mg/kg, mg/kg = ppm
- Photo is included.

.....



REPORT No.: R2DG2001132326E Date: January 16, 2020 Page 5 of 5







BACL authenticate the photo on original report only

Directions:

- 1. This report cannot be reproduced except in full, without prior written approval of the Company.
- 2. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
- 3. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.
- 4. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
- 5. The information which provided by the applicant, such as sample description, sample name ,material component, style/item No. , P.O. No. , manufacture, age phase, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report.
- 6. The test samples were in good condition before testing.
- 7. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

*** End of Report ***